



C4000 Select Safety Light Curtain

Flexible Solutions for Machine Safeguarding

SICK
Sensor Intelligence.

...at the Speed of Light

The C4000 Select safety light curtain is designed specifically to meet the requirements of our North American customers. It is configured using DIP switches, rather than a PC, and provides intuitive and visible diagnostics for fast troubleshooting. Plus, the integrated laser and alignment bar graph display simplifies commissioning and an optional LED indicator provides continuous status indication – even from a distance.

Versatility... at the speed of light

- Reduce installation and start up time – flexible mounting options, and integrated laser alignment
- Simplify maintenance – complete, visible diagnostics for troubleshooting
- Maximize machine availability – on-the-spot replacement and alignment indicators
- Extended I/O – provides a single set of outputs to simplify wiring
- Cascade other C4000 Select light curtains or a S300 or S3000 safety laser scanners



AUTOMOTIVE

Reduced maintenance and installation costs. The C4000 Select is ideal for automotive manufacturing, such as safeguarding stamping presses and turntable applications.



MATERIAL HANDLING

Versatility. In applications involving automatic material transport, the C4000 Select offers point-of-entry and point-of-operation safeguarding for conveyors, palletizing and specialty machines.



ROBOTICS

Flexibility. The C4000 Select can be cascaded with a S300 or S3000 safety laser scanner or with other C4000 Select Light Curtains to provide complete safeguarding of a robotic work cell with a single safety signal.



Technical Specifications




General system data	
Sensing range (low/high)	30 mm: 0 ...6 m/ 5...19 m 14 mm: 0 ...2.5 m/2 ...8 m
Protective field height (depending on type)	300, 450, 600, 750, 900, 1050, 1200, 1350, 1500, 1650, 1800 mm
Resolution (depending on type)	30, 14 mm
Protection class	III
Enclosure rating	IP 65
Supply voltage U_V	24 V (19.2 V...28.8 V) DC ¹⁾
Type	Type 4, according to IEC 61496, SIL3 (IEC/EN 62061), PL e (ISO 13849-1:2006)
Synchronization	Optical, without separate synchronization
Operating data	
Connection type	M12 x 5
Ambient operating temperature from... to	0...55° C
Storage temperature from... to	-25...70° C
Air humidity from... to	15...95%
Housing cross-section	52 mm x 55.5 mm
Vibration resistance	5 g, 10...55 Hz according to IEC 60068-2-6
Shock resistance	10 g, 16 ms IEC 60068-2-29

¹⁾ The external voltage supply must be capable of buffering brief mains failures of 20 ms as specified in EN 60 204-1. Suitable power supplies are available as accessories from SICK.

MACHINE TOOLS

Simple and intuitive operation.
Commissioning time with the C4000 Select is minimized with its integrated laser alignment and no need for software programming. It is ideal for point-of-operation safeguarding on metal working machines.



PACKAGING

Safety and availability.
The C4000 Select offers a high degree of safety and production throughput for packaging lines and machines. In addition, the C4000 is easy to integrate and offers the best response times in the industry.



SafetyPlus

SICK provides a whole system approach to safety, including assessments, consulting services and engineering support. From design... through operation... to retrofitting, our goal is to solve your application efficiently and cost-effectively.



Ordering Information

C4000 Select without Extension Connection				
Protective Field Height (mm)	Resolution (mm)	Part Numbers and Model Designations		
		Sender Only	Receiver Only	Sender and Receiver
300	14	1208918 (XC40S-0301A0A00AAA0)	1208951 (XC40E-0301A0A0AAA0)	1052742 (XC40P-0301A0A0AAA0)
	30	1204061 (XC40S-0303A0A00AAA0)	1204063 (XC40E-0303A0A0AAA0)	1043111 (XC40P-0303A0A0AAA0)
450	14	1208825 (XC40S-0401A0A00AAA0)	1208824 (XC40E-0401A0A0AAA0)	1052743 (XC40P-0401A0A0AAA0)
	30	1208853 (XC40S-0403A0A00AAA0)	1208852 (XC40E-0403A0A0AAA0)	1052707 (XC40P-0403A0A0AAA0)
600	14	1208919 (XC40S-0601A0A00AAA0)	1208952 (XC40E-0601A0A0AAA0)	1052744 (XC40P-0601A0A0AAA0)
	30	1204068 (XC40S-0603A0A00AAA0)	1204116 (XC40E-0603A0A0AAA0)	1043112 (XC40P-0603A0A0AAA0)
750	14	1208920 (XC40S-0701A0A00AAA0)	1208953 (XC40E-0701A0A0AAA0)	1052745 (XC40P-0701A0A0AAA0)
	30	1208855 (XC40S-0703A0A00AAA0)	1208854 (XC40E-0703A0A0AAA0)	1052708 (XC40P-0703A0A0AAA0)
900	14	1208921 (XC40S-0901A0A00AAA0)	1208954 (XC40E-0901A0A0AAA0)	1052746 (XC40P-0901A0A0AAA0)
	30	1204071 (XC40S-0903A0A00AAA0)	1204191 (XC40E-0903A0A0AAA0)	1043113 (XC40P-0903A0A0AAA0)
1050	14	1208922 (XC40S-1001A0A00AAA0)	1208955 (XC40E-1001A0A0AAA0)	1052747 (XC40P-1001A0A0AAA0)
	30	1208856 (XC40S-1003A0A00AAA0)	1208857 (XC40E-1003A0A0AAA0)	1052709 (XC40P-1003A0A0AAA0)
1200	14	1208923 (XC40S-1201A0A00AAA0)	1208956 (XC40E-1201A0A0AAA0)	1052748 (XC40P-1201A0A0AAA0)
	30	1204118 (XC40S-1203A0A00AAA0)	1204102 (XC40E-1203A0A0AAA0)	1043114 (XC40P-1203A0A0AAA0)
1350	14	1208924 (XC40S-1301A0A00AAA0)	1208957 (XC40E-1301A0A0AAA0)	1052749 (XC40P-1301A0A0AAA0)
	30	1208858 (XC40S-1303A0A00AAA0)	1208859 (XC40E-1303A0A0AAA0)	1052710 (XC40P-1303A0A0AAA0)
1500	14	1208925 (XC40S-1501A0A00AAA0)	1208958 (XC40E-1501A0A0AAA0)	1052750 (XC40P-1501A0A0AAA0)
	30	1204119 (XC40S-1503A0A00AAA0)	1204137 (XC40E-1503A0A0AAA0)	1043115 (XC40P-1503A0A0AAA0)
1650	14	1208926 (XC40S-1601A0A00AAA0)	1208959 (XC40E-1601A0A0AAA0)	1052751 (XC40P-1601A0A0AAA0)
	30	1208860 (XC40S-1603A0A00AAA0)	1208861 (XC40E-1603A0A0AAA0)	1052711 (XC40P-1603A0A0AAA0)
1800	14	1208927 (XC40S-1801A0A00AAA0)	1208960 (XC40E-1801A0A0AAA0)	1052752 (XC40P-1801A0A0AAA0)
	30	1204112 (XC40S-1803A0A00AAA0)	1204138 (XC40E-1803A0A0AAA0)	1043116 (XC40P-1803A0A0AAA0)

C4000 Select with Integrated LED Indicator Lamp				
Protective Field Height (mm)	Resolution (mm)	Part Numbers and Model Designations		
		Sender Only	Receiver Only	Sender and Receiver
300	14	1208918 (XC40S-0301A0A00AAA0)	1208961 (XC40E-0301A0A0AAC0)	1052753 (XC40P-0301A0A0AAC0)
	30	1204061 (XC40S-0303A0A00AAA0)	1204139 (XC40E-0303A0A0AAC0)	1043117 (XC40P-0303A0A0AAC0)
450	14	1208825 (XC40S-0401A0A00AAA0)	1208962 (XC40E-0401A0A0AAC0)	1052754 (XC40P-0401A0A0AAC0)
	30	1208853 (XC40S-0403A0A00AAA0)	1208862 (XC40E-0403A0A0AAC0)	1052712 (XC40P-0403A0A0AAC0)
600	14	1208919 (XC40S-0601A0A00AAA0)	1208963 (XC40E-0601A0A0AAC0)	1052755 (XC40P-0601A0A0AAC0)
	30	1204068 (XC40S-0603A0A00AAA0)	1204140 (XC40E-0603A0A0AAC0)	1043118 (XC40P-0603A0A0AAC0)
750	14	1208920 (XC40S-0701A0A00AAA0)	1208964 (XC40E-0701A0A0AAC0)	1052756 (XC40P-0701A0A0AAC0)
	30	1208855 (XC40S-0703A0A00AAA0)	1208863 (XC40E-0703A0A0AAC0)	1052713 (XC40P-0703A0A0AAC0)
900	14	1208921 (XC40S-0901A0A00AAA0)	1208965 (XC40E-0901A0A0AAC0)	1052757 (XC40P-0901A0A0AAC0)
	30	1204071 (XC40S-0903A0A00AAA0)	1204141 (XC40E-0903A0A0AAC0)	1043119 (XC40P-0903A0A0AAC0)
1050	14	1208922 (XC40S-1001A0A00AAA0)	1208966 (XC40E-1001A0A0AAC0)	1052758 (XC40P-1001A0A0AAC0)
	30	1208856 (XC40S-1003A0A00AAA0)	1208864 (XC40E-1003A0A0AAC0)	1052714 (XC40P-1003A0A0AAC0)
1200	14	1208923 (XC40S-1201A0A00AAA0)	1208967 (XC40E-1201A0A0AAC0)	1052759 (XC40P-1201A0A0AAC0)
	30	1204118 (XC40S-1203A0A00AAA0)	1204142 (XC40E-1203A0A0AAC0)	1043120 (XC40P-1203A0A0AAC0)
1350	14	1208924 (XC40S-1301A0A00AAA0)	1208968 (XC40E-1301A0A0AAC0)	1052760 (XC40P-1301A0A0AAC0)
	30	1208858 (XC40S-1303A0A00AAA0)	1208865 (XC40E-1303A0A0AAC0)	1052715 (XC40P-1303A0A0AAC0)
1500	14	1208925 (XC40S-1501A0A00AAA0)	1208969 (XC40E-1501A0A0AAC0)	1052761 (XC40P-1501A0A0AAC0)
	30	1204119 (XC40S-1503A0A00AAA0)	1204143 (XC40E-1503A0A0AAC0)	1043121 (XC40P-1503A0A0AAC0)
1650	14	1208926 (XC40S-1601A0A00AAA0)	1208970 (XC40E-1601A0A0AAC0)	1052762 (XC40P-1601A0A0AAC0)
	30	1208860 (XC40S-1603A0A00AAA0)	1208866 (XC40E-1603A0A0AAC0)	1052716 (XC40P-1603A0A0AAC0)
1800	14	1208927 (XC40S-1801A0A00AAA0)	1208971 (XC40E-1801A0A0AAC0)	1052763 (XC40P-1801A0A0AAC0)
	30	1204112 (XC40S-1803A0A00AAA0)	1204144 (XC40E-1803A0A0AAC0)	1043122 (XC40P-1803A0A0AAC0)

C4000 Select with Top Endcap Extension				
Protective Field Height (mm)	Resolution (mm)	Part Numbers and Model Designations		
		Sender Only	Receiver Only	Sender and Receiver
300	14	z (XC40S-0301A0A00AAA0)	z (XC40E-0301A0A0AAA0)	z (XC40P-0301A0A0AAA0)
	30	z (XC40S-0303A0A00AAA0)	z (XC40E-0303A0A0AAA0)	z (XC40P-0303A0A0AAA0)
450	14	z (XC40S-0401A0A00AAA0)	z (XC40E-0401A0A0AAA0)	z (XC40P-0401A0A0AAA0)
	30	z (XC40S-0403A0A00AAA0)	z (XC40E-0403A0A0AAA0)	z (XC40P-0403A0A0AAA0)
600	14	z (XC40S-0601A0A00AAA0)	z (XC40E-0601A0A0AAA0)	z (XC40P-0601A0A0AAA0)
	30	z (XC40S-0603A0A00AAA0)	z (XC40E-0603A0A0AAA0)	z (XC40P-0603A0A0AAA0)
750	14	z (XC40S-0701A0A00AAA0)	z (XC40E-0701A0A0AAA0)	z (XC40P-0701A0A0AAA0)
	30	z (XC40S-0703A0A00AAA0)	z (XC40E-0703A0A0AAA0)	z (XC40P-0703A0A0AAA0)
900	14	z (XC40S-0901A0A00AAA0)	z (XC40E-0901A0A0AAA0)	z (XC40P-0901A0A0AAA0)
	30	z (XC40S-0903A0A00AAA0)	z (XC40E-0903A0A0AAA0)	z (XC40P-0903A0A0AAA0)
1050	14	z (XC40S-1001A0A00AAA0)	z (XC40E-1001A0A0AAA0)	z (XC40P-1001A0A0AAA0)
	30	z (XC40S-1003A0A00AAA0)	z (XC40E-1003A0A0AAA0)	z (XC40P-1003A0A0AAA0)
1200	14	z (XC40S-1201A0A00AAA0)	z (XC40E-1201A0A0AAA0)	z (XC40P-1201A0A0AAA0)
	30	z (XC40S-1203A0A00AAA0)	z (XC40E-1203A0A0AAA0)	z (XC40P-1203A0A0AAA0)
1350	14	z (XC40S-1301A0A00AAA0)	z (XC40E-1301A0A0AAA0)	z (XC40P-1301A0A0AAA0)
	30	z (XC40S-1303A0A00AAA0)	z (XC40E-1303A0A0AAA0)	z (XC40P-1303A0A0AAA0)
1500	14	z (XC40S-1501A0A00AAA0)	z (XC40E-1501A0A0AAA0)	z (XC40P-1501A0A0AAA0)
	30	z (XC40S-1503A0A00AAA0)	z (XC40E-1503A0A0AAA0)	z (XC40P-1503A0A0AAA0)
1650	14	z (XC40S-1601A0A00AAA0)	z (XC40E-1601A0A0AAA0)	z (XC40P-1601A0A0AAA0)
	30	z (XC40S-1603A0A00AAA0)	z (XC40E-1603A0A0AAA0)	z (XC40P-1603A0A0AAA0)
1800	14	z (XC40S-1801A0A00AAA0)	z (XC40E-1801A0A0AAA0)	z (XC40P-1801A0A0AAA0)
	30	z (XC40S-1803A0A00AAA0)	z (XC40E-1803A0A0AAA0)	z (XC40P-1803A0A0AAA0)

C4000 Select with Bottom Endcap Extension on Both Sender and Receiver				
Protective Field Height (mm)	Resolution (mm)	Part Numbers and Model Designations		
		Sender Only	Receiver Only	Sender and Receiver
300	14	1208939 (XC40S-0301A0A00BAA0)	1208983 (XC40E-0301A0A00CBA0)	1052775 (XC40P-0301A0A00CBA0)
	30	1204154 (XC40S-0303A0A00BAA0)	1204155 (XC40E-0303A0A00CBA0)	1043129 (XC40P-0303A0A00CBA0)
450	14	1208940 (XC40S-0401A0A00BAA0)	1208984 (XC40E-0401A0A00CBA0)	1052776 (XC40P-0401A0A00CBA0)
	30	1208877 (XC40S-0403A0A00BAA0)	1208878 (XC40E-0403A0A00CBA0)	1052722 (XC40P-0403A0A00CBA0)
600	14	1208941 (XC40S-0601A0A00BAA0)	1208985 (XC40E-0601A0A00CBA0)	1052777 (XC40P-0601A0A00CBA0)
	30	1204156 (XC40S-0603A0A00BAA0)	1204157 (XC40E-0603A0A00CBA0)	1043130 (XC40P-0603A0A00CBA0)
750	14	1208942 (XC40S-0701A0A00BAA0)	1208986 (XC40E-0701A0A00CBA0)	1052778 (XC40P-0701A0A00CBA0)
	30	1208879 (XC40S-0703A0A00BAA0)	1208894 (XC40E-0703A0A00CBA0)	1052723 (XC40P-0703A0A00CBA0)
900	14	1208944 (XC40S-0901A0A00BAA0)	1208987 (XC40E-0901A0A00CBA0)	1052779 (XC40P-0901A0A00CBA0)
	30	1204158 (XC40S-0903A0A00BAA0)	1204159 (XC40E-0903A0A00CBA0)	1043131 (XC40P-0903A0A00CBA0)
1050	14	1208943 (XC40S-1001A0A00BAA0)	1208988 (XC40E-1001A0A00CBA0)	1052780 (XC40P-1001A0A00CBA0)
	30	1208880 (XC40S-1003A0A00BAA0)	1208881 (XC40E-1003A0A00CBA0)	1052724 (XC40P-1003A0A00CBA0)
1200	14	1208945 (XC40S-1201A0A00BAA0)	1208989 (XC40E-1201A0A00CBA0)	1052781 (XC40P-1201A0A00CBA0)
	30	1204160 (XC40S-1203A0A00BAA0)	1204161 (XC40E-1203A0A00CBA0)	1043132 (XC40P-1203A0A00CBA0)
1350	14	1208946 (XC40S-1301A0A00BAA0)	1208990 (XC40E-1301A0A00CBA0)	1052782 (XC40P-1301A0A00CBA0)
	30	1208882 (XC40S-1303A0A00BAA0)	1208883 (XC40E-1303A0A00CBA0)	1052725 (XC40P-1303A0A00CBA0)
1500	14	1208947 (XC40S-1501A0A00BAA0)	1208991 (XC40E-1501A0A00CBA0)	1052783 (XC40P-1501A0A00CBA0)
	30	1204162 (XC40S-1503A0A00BAA0)	1204163 (XC40E-1503A0A00CBA0)	1043133 (XC40P-1503A0A00CBA0)
1650	14	1208948 (XC40S-1601A0A00BAA0)	1208992 (XC40E-1601A0A00CBA0)	1052784 (XC40P-1601A0A00CBA0)
	30	1208884 (XC40S-1603A0A00BAA0)	1208885 (XC40E-1603A0A00CBA0)	1052726 (XC40P-1603A0A00CBA0)
1800	14	1208949 (XC40S-1801A0A00BAA0)	1208993 (XC40E-1801A0A00CBA0)	1052785 (XC40P-1801A0A00CBA0)
	30	1204164 (XC40S-1803A0A00BAA0)	1204165 (XC40E-1803A0A00CBA0)	1043134 (XC40P-1803A0A00CBA0)

C4000 Select with Bottom Endcap Extension on Both Sender and Receiver and Indicator Lamp on Receiver

Protective Field Height (mm)	Resolution (mm)	Part Numbers and Model Designations		
		Sender Only	Receiver Only	Sender and Receiver
300	14	1208939 (XC40S-0301A0A00BA0)	1208994 (XC40E-0301A0A00CBC0)	1052786 (XC40P-0301A0A00CBC0)
	30	1204154 (XC40S-0303A0A00BA0)	1204166 (XC40E-0303A0A00CBC0)	1043135 (XC40P-0303A0A00CBC0)
450	14	1208940 (XC40S-0401A0A00BA0)	1208995 (XC40E-0401A0A00CBC0)	1052787 (XC40P-0401A0A00CBC0)
	30	1208877 (XC40S-0403A0A00BAA0)	1208950 (XC40E-0403A0A00CBC0)	1052727 (XC40P-0403A0A00CBC0)
600	14	1208941 (XC40S-0601A0A00BA0)	1208996 (XC40E-0601A0A00CBC0)	1052788 (XC40P-0601A0A00CBC0)
	30	1204156 (XC40S-0603A0A00BA0)	1204167 (XC40E-0603A0A00CBC0)	1043136 (XC40P-0603A0A00CBC0)
750	14	1208942 (XC40S-0701A0A00BA0)	1208997 (XC40E-0701A0A00CBC0)	1052789 (XC40P-0701A0A00CBC0)
	30	1208879 (XC40S-0703A0A00BA0)	1208886 (XC40E-0703A0A00CBC0)	1052728 (XC40P-0703A0A00CBC0)
900	14	1208944 (XC40S-0901A0A00BA0)	1208998 (XC40E-0901A0A00CBC0)	1052790 (XC40P-0901A0A00CBC0)
	30	1204158 (XC40S-0903A0A00BA0)	1204168 (XC40E-0903A0A00CBC0)	1043137 (XC40P-0903A0A00CBC0)
1050	14	1208943 (XC40S-1001A0A00BA0)	1208999 (XC40E-1001A0A00CBC0)	1052791 (XC40P-1001A0A00CBC0)
	30	1208880 (XC40S-1003A0A00BA0)	1208887 (XC40E-1003A0A00CBC0)	1052729 (XC40P-1003A0A00CBC0)
1200	14	1208945 (XC40S-1201A0A00BA0)	1209000 (XC40E-1201A0A00CBC0)	1052792 (XC40P-1201A0A00CBC0)
	30	1204160 (XC40S-1203A0A00BA0)	1204169 (XC40E-1203A0A00CBC0)	1043138 (XC40P-1203A0A00CBC0)
1350	14	1208946 (XC40S-1301A0A00BA0)	1209001 (XC40E-1301A0A00CBC0)	1052793 (XC40P-1301A0A00CBC0)
	30	1208882 (XC40S-1303A0A00BA0)	1208888 (XC40E-1303A0A00CBC0)	1052730 (XC40P-1303A0A00CBC0)
1500	14	1208947 (XC40S-1501A0A00BA0)	1209002 (XC40E-1501A0A00CBC0)	1052794 (XC40P-1501A0A00CBC0)
	30	1204162 (XC40S-1503A0A00BA0)	1204170 (XC40E-1503A0A00CBC0)	1043139 (XC40P-1503A0A00CBC0)
1650	14	1208948 (XC40S-1601A0A00BA0)	1209003 (XC40E-1601A0A00CBC0)	1052795 (XC40P-1601A0A00CBC0)
	30	1208884 (XC40S-1603A0A00BA0)	1208889 (XC40E-1603A0A00CBC0)	1052731 (XC40P-1603A0A00CBC0)
1800	14	1208949 (XC40S-1801A0A00BA0)	1209004 (XC40E-1801A0A00CBC0)	1052796 (XC40P-1801A0A00CBC0)
	30	1204164 (XC40S-1803A0A00BA0)	1204171 (XC40E-1803A0A00CBC0)	1043140 (XC40P-1803A0A00CBC0)

C4000 Select with Bottom Endcap Extension on the Receiver Only

Protective Field Height (mm)	Resolution (mm)	Part Numbers and Model Designations		
		Sender Only	Receiver Only	Sender and Receiver
300	14	1208918 (XC40S-0301A0A00AA0)	1208983 (XC40E-0301A0A00CBA0)	1052797 (XC40P-0301A0A00CCA0)
	30	1204061 (XC40S-0303A0A00AA0)	1204155 (XC40E-0303A0A00CBA0)	1043141 (XC40P-0303A0A00CCA0)
450	14	1208825 (XC40S-0401A0A00AA0)	1208984 (XC40E-0401A0A00CBA0)	1052798 (XC40P-0401A0A00CCA0)
	30	1208853 (XC40S-0403A0A00AAA0)	1208878 (XC40E-0403A0A00CBA0)	1052732 (XC40P-0403A0A00CCA0)
600	14	1208919 (XC40S-0601A0A00AA0)	1208985 (XC40E-0601A0A00CBA0)	1052799 (XC40P-0601A0A00CCA0)
	30	1204068 (XC40S-0603A0A00AA0)	1204157 (XC40E-0603A0A00CBA0)	1043142 (XC40P-0603A0A00CCA0)
750	14	1208920 (XC40S-0701A0A00AA0)	1208986 (XC40E-0701A0A00CBA0)	1052800 (XC40P-0701A0A00CCA0)
	30	1208855 (XC40S-0703A0A00AA0)	1208894 (XC40E-0703A0A00CBA0)	1052733 (XC40P-0703A0A00CCA0)
900	14	1208921 (XC40S-0901A0A00AA0)	1208987 (XC40E-0901A0A00CBA0)	1052801 (XC40P-0901A0A00CCA0)
	30	1204071 (XC40S-0903A0A00AA0)	1204159 (XC40E-0903A0A00CBA0)	1043143 (XC40P-0903A0A00CCA0)
1050	14	1208922 (XC40S-1001A0A00AA0)	1208988 (XC40E-1001A0A00CBA0)	1052802 (XC40P-1001A0A00CCA0)
	30	1208856 (XC40S-1003A0A00AA0)	1208881 (XC40E-1003A0A00CBA0)	1052734 (XC40P-1003A0A00CCA0)
1200	14	1208923 (XC40S-1201A0A00AA0)	1208989 (XC40E-1201A0A00CBA0)	1052803 (XC40P-1201A0A00CCA0)
	30	1204118 (XC40S-1203A0A00AA0)	1204161 (XC40E-1203A0A00CBA0)	1043144 (XC40P-1203A0A00CCA0)
1350	14	1208924 (XC40S-1301A0A00AA0)	1208990 (XC40E-1301A0A00CBA0)	1052804 (XC40P-1301A0A00CCA0)
	30	1208858 (XC40S-1303A0A00AA0)	1208883 (XC40E-1303A0A00CBA0)	1052735 (XC40P-1303A0A00CCA0)
1500	14	1208925 (XC40S-1501A0A00AA0)	1208991 (XC40E-1501A0A00CBA0)	1052805 (XC40P-1501A0A00CCA0)
	30	1204119 (XC40S-1503A0A00AA0)	1204163 (XC40E-1503A0A00CBA0)	1043145 (XC40P-1503A0A00CCA0)
1650	14	1208926 (XC40S-1601A0A00AA0)	1208992 (XC40E-1601A0A00CBA0)	1052806 (XC40P-1601A0A00CCA0)
	30	1208860 (XC40S-1603A0A00AA0)	1208885 (XC40E-1603A0A00CBA0)	1052736 (XC40P-1603A0A00CCA0)
1800	14	1208927 (XC40S-1801A0A00AA0)	1208993 (XC40E-1801A0A00CBA0)	1052807 (XC40P-1801A0A00CCA0)
	30	1204112 (XC40S-1803A0A00AA0)	1204165 (XC40E-1803A0A00CBA0)	1043146 (XC40P-1803A0A00CCA0)


C4000 Select with Bottom Endcap Extension and Integrated LED Indicator Lamp on the Receiver Only

Protective Field Height (mm)	Resolution (mm)	Part Numbers and Model Designations		
		Sender Only	Receiver Only	Sender and Receiver
300	14	1208918 (XC40S-0301A0A00AAA0)	1208994 (XC40E-0301A0A0CBC0)	1052808 (XC40P-0301A0A0CCCC0)
	30	1204061 (XC40S-0303A0A00AAA0)	1204166 (XC40E-0303A0A0CBC0)	1043147 (XC40P-0303A0A0CCCC0)
450	14	1208825 (XC40S-0401A0A00AAA0)	1208995 (XC40E-0401A0A0CBC0)	1052809 (XC40P-0401A0A0CCCC0)
	30	1208853 (XC40S-0403A0A0AAA0)	1208950 (XC40E-0403A0A0CBC0)	1052737 (XC40P-0403A0A0CCCC0)
600	14	1208919 (XC40S-0601A0A00AAA0)	1208996 (XC40E-0601A0A0CBC0)	1052810 (XC40P-0601A0A0CCCC0)
	30	1204068 (XC40S-0603A0A00AAA0)	1204167 (XC40E-0603A0A0CBC0)	1043148 (XC40P-0603A0A0CCCC0)
750	14	1208920 (XC40S-0701A0A00AAA0)	1208997 (XC40E-0701A0A0CBC0)	1052811 (XC40P-0701A0A0CCCC0)
	30	1208855 (XC40S-0703A0A00AAA0)	1208886 (XC40E-0703A0A0CBC0)	1052738 (XC40P-0703A0A0CCCC0)
900	14	1208921 (XC40S-0901A0A00AAA0)	1208998 (XC40E-0901A0A0CBC0)	1052812 (XC40P-0901A0A0CCCC0)
	30	1204071 (XC40S-0903A0A00AAA0)	1204168 (XC40E-0903A0A0CBC0)	1043149 (XC40P-0903A0A0CCCC0)
1050	14	1208922 (XC40S-1001A0A00AAA0)	1208999 (XC40E-1001A0A0CBC0)	1052813 (XC40P-1001A0A0CCCC0)
	30	1208856 (XC40S-1003A0A00AAA0)	1208887 (XC40E-1003A0A0CBC0)	1052739 (XC40P-1003A0A0CCCC0)
1200	14	1208923 (XC40S-1201A0A00AAA0)	1209000 (XC40E-1201A0A0CBC0)	1052814 (XC40P-1201A0A0CCCC0)
	30	1204118 (XC40S-1203A0A00AAA0)	1204169 (XC40E-1203A0A0CBC0)	1043150 (XC40P-1203A0A0CCCC0)
1350	14	1208924 (XC40S-1301A0A00AAA0)	1209001 (XC40E-1301A0A0CBC0)	1052815 (XC40P-1301A0A0CCCC0)
	30	1208858 (XC40S-1303A0A00AAA0)	1208888 (XC40E-1303A0A0CBC0)	1052740 (XC40P-1303A0A0CCCC0)
1500	14	1208925 (XC40S-1501A0A00AAA0)	1209002 (XC40E-1501A0A0CBC0)	1052816 (XC40P-1501A0A0CCCC0)
	30	1204119 (XC40S-1503A0A00AAA0)	1204170 (XC40E-1503A0A0CBC0)	1043151 (XC40P-1503A0A0CCCC0)
1650	14	1208926 (XC40S-1601A0A00AAA0)	1209003 (XC40E-1601A0A0CBC0)	1052817 (XC40P-1601A0A0CCCC0)
	30	1208860 (XC40S-1603A0A00AAA0)	1208889 (XC40E-1603A0A0CBC0)	1052741 (XC40P-1603A0A0CCCC0)
1800	14	1208927 (XC40S-1801A0A00AAA0)	1209004 (XC40E-1801A0A0CBC0)	1052818 (XC40P-1801A0A0CCCC0)
	30	1204112 (XC40S-1803A0A00AAA0)	1204171 (XC40E-1803A0A0CBC0)	1043152 (XC40P-1803A0A0CCCC0)

Accessories

Part	Part Number
System connection cables	
M12 x 5 connection cable, single-ended female connection with flying leads	
Plug straight/stripped, 2 m	6008899
Plug straight/stripped, 5 m	6009868
Plug straight/stripped, 10 m	6010544
Plug straight/stripped, 15 m	6029215
Plug straight/stripped, 30 m	6032956
Extension connection cables for extended I/O	
Used for cascade connection between a host/guest 1 C4000 Select extension connection and subsequent C4000 Select guest 1/guests 2 system connection	
M12 x 5 connection cable, double-ended connections, male and female for extended I/O connection of a C4000 Select	
Plug straight/plug straight, 0.6 m	6025930
Plug straight/plug straight, 1 m	6029280
Plug straight/plug straight, 2 m	6025931
Plug straight/plug straight, 5 m	6029282
M12 x 5 connection cable, single-ended male connection with flying leads for extended I/O connection of S300 or S3000	
Plug straight/plug straight, 2 m	6026133
Plug straight/plug straight, 5 m	6026134
Plug straight/plug straight, 10 m	6026135
Mounting brackets	
Swivel mounting bracket kit (mounting kit 12)	2030510
Side mounting bracket kit (mounting kit 6)	2019506
Standard "L" type mounting bracket kit	7021352

SICK at a glance



Leading technologies

With a staff of more than 5,000 and over 50 subsidiaries and representations worldwide, SICK is one of the leading and most successful manufacturers of sensor technology. The power of innovation and solution competency have made SICK the global market leader. No matter what the project and industry may be, talking with an expert from SICK will provide you with an ideal basis for your plans – there is no need to settle for anything less than the best.



Unique product range

- Non-contact detecting, counting, classifying and positioning of any type of object
- Accident and operator protection with sensors, safety software and services
- Automatic identification with bar code and RFID readers
- Laser measurement technology for detecting the volume, position and contour of people and objects
- Complete system solutions for analysis and flow measurement of gases and liquids



Comprehensive services

- SICK LifeTime Services – for safety and productivity
- Application centers in Europe, Asia and North America for the development of system solutions under real-world conditions
- E-Business Partner Portal www.mysick.com – price and availability of products, requests for quotation and online orders

Worldwide presence with subsidiaries in the following countries:

Australia
Belgium/Luxembourg
Brasil
Ceská Republika
China
Danmark
Deutschland
España
France
Great Britain
India
Israel
Italia

Japan
Nederland
Norge
Österreich
Polska
Republic of Korea
România
Russia
Schweiz
Singapore
South Africa
Suomi
Sverige
Taiwan
Türkiye
United Arab Emirates
USA/Canada/México

Please find detailed addresses and additional representatives and agencies in all major industrial nations at www.sick.com