



6ES7212-1HD30-0XB0 CPU 1212C 8DI/6DO/2AI

Technical / CAx data

Technical Data  CAx data

**SIMATIC S7-1200, CPU 1212C, COMPACT CPU, DC/DC/RLY, ONBOARD I/O: 8 DI 24V DC; 6 DO RELAY 2A; 2 AI 0 - 10V DC, POWER SUPPLY: AC 20.4 - 28.8 V DC, PROGRAM/DATA MEMORY: 25 KB**

**Product version**

**associated programming package** STEP 7 Basic V10.5

**Supply voltages**

**Rated value**

**24 V DC** Yes

**permissible range, lower limit (DC)** 20.4 V

**permissible range, upper limit (DC)** 28.8 V

**Load voltage L+**

**Rated value (DC)** 24 V

**permissible range, lower limit (DC)** 5 V

**permissible range, upper limit (DC)** 250 V

**Current consumption**

**Current consumption (rated value)** 175 mA; Typical

**Current consumption, max.** 1.2 A; 24 VDC

**Inrush current, max.** 12 A; At 28.8 V

**Current output to backplane bus (DC 5 V), max.** 1000 mA; 5 VDC max. for SM and CM

**Power losses**

**Power loss, typ.** 9 W

**Memory**

**Usable memory for user data** 25 kbyte

**Work memory**

**integrated** 25 kbyte

**expandable** No

**Load memory**

**integrated** 1 Mbyte; Load memory expandable using SIEMENS Memory Card

**expandable, max.** 24 Mbyte; with SIEMENS Memory Card

**Backup**

**present** Yes; entire project maintenance-free in the integral EEPROM

**without battery** Yes

**CPU/ blocks**

**OB**

**Number, max.** Limited only by RAM for code

**CPU processing times**

**for bit operations, min.** 0.1 µs; / instruction

**for word operations, min.** 12 µs; / instruction

**for floating point arithmetic, min.** 18 µs; / instruction

**Data areas and their retentivity**

**retentive data area in total (incl. times, counters,** 2048 byte

flags), max.

**Flag**

**Number, max.** 4 kbyte; Size of bit memory address area

**Address area**

**I/O address area**

**I/O address area, overall** 1024 bytes for inputs / 1024 bytes for outputs

**Inputs** 1024 byte

**Outputs** 1024 byte

**Process image**

**Inputs, adjustable** 1 kbyte

**Outputs, adjustable** 1 kbyte

**Digital channels**

**integrated channels (DI)** 8

**integrated channels (DO)** 6

**Analog channels**

**Integrated channels (AI)** 2

**Number of integrated channels (AO)** 0

**Hardware configuration**

**Number of modules per system, max.** 3 comm. modules, 1 signal board, 2 signal modules

**Time of day**

**Clock**

**Hardware clock (real-time clock)** Yes

**Backup time** 240 h; Typical

**Deviation per day, max.** 60 s/month @ 25°C

**Test commissioning functions**

**Status/control**

**Status/control variable** Yes

**Variables** Inputs/outputs, memory bits, DB, distributed I/Os, timers, counters

**Forcing**

**Forcing** Yes

**Communication functions**

**S7 communication**

**supported** Yes

**as server** Yes

**Open IE communication**

**TCP/IP** Yes

**ISO-on-TCP (RFC1006)** Yes

**Number of connections**

**overall** 15; dynamically

**1st interface**

**Type of interface** PROFINET

**Physics** Ethernet

**Isolated** Yes

**automatic detection of transmission speed** Yes

**Autonegotiation** Yes

**Autocrossing** Yes

**CPU/ programming**

**Configuration software**

<b>STEP 7</b>	STEP 7 Basic V10.5
<b>Programming language</b>	
<b>LAD</b>	Yes
<b>FBD</b>	Yes
<b>Cycle time monitoring can be set</b>	Yes
<b>Digital inputs</b>	
<b>Number of digital inputs</b>	8; Integrated
<b>of which, inputs usable for technological functions</b>	4; HSC (High Speed Counting)
<b>m/p-reading</b>	Yes
<b>Input voltage</b>	
<b>Rated value, DC</b>	24 V
<b>for signal "0"</b>	5 VDC at 1 mA
<b>for signal "1"</b>	15 VDC at 2.5 mA
<b>Input current</b>	
<b>for signal "1", typ.</b>	1 mA
<b>Input delay (for rated value of input voltage)</b>	
<b>for standard inputs parameterizable</b>	0.2, 0.4, 0.8, 1.6, 3.2, 6.4, and 12.8 ms, selectable in groups of four
<b>at "0" to "1", min.</b>	0.2 ms
<b>at "0" to "1", max.</b>	12.8 ms
<b>for interrupt inputs parameterizable</b>	Yes
<b>Cable length</b>	
<b>Cable length, shielded, max.</b>	500 m; 50 m for technological functions
<b>Cable length unshielded, max.</b>	300 m; For technological functions: No
<b>Digital outputs</b>	
<b>Number of digital outputs</b>	6; Relay
<b>Short-circuit protection of the output</b>	No; to be provided externally
<b>Switching capacity of the outputs</b>	
<b>with resistive load, max.</b>	2 A
<b>on lamp load, max.</b>	30 W DC; 200 W AC
<b>Output delay with resistive load</b>	
<b>0 to "1", max.</b>	10 ms; max.
<b>1 to "0", max.</b>	10 ms; max.
<b>Switching frequency of the pulse outputs, with resistive load, max.</b>	1 Hz
<b>Cable length</b>	
<b>Cable length, shielded, max.</b>	500 m
<b>Cable length unshielded, max.</b>	150 m
<b>Relay outputs</b>	
<b>Number of relay outputs</b>	6
<b>Number of operating cycles</b>	mechanically 10 million, at rated load voltage 100,000
<b>Analog inputs</b>	
<b>Number of analog inputs</b>	2
<b>Cable length, shielded, max.</b>	100 m; twisted and shielded
<b>Input ranges</b>	
<b>Voltage</b>	Yes
<b>Input ranges (rated values), voltages</b>	

<b>0 to +10 V</b>	Yes
<b>Input resistance (0 to 10 V)</b>	≥100k ohms
<b>Analog outputs</b>	
<b>Cable length</b>	10 m; twisted
<b>Analog value creation</b>	
<b>Integrations and conversion time/ resolution per channel</b>	
<b>Resolution with overrange (bit including sign), max.</b>	10 bit
<b>Integration time, parameterizable</b>	Yes
<b>Conversion time (per channel)</b>	625 µs
<b>Encoder supply</b>	
<b>24 V encoder supply</b>	
<b>24 V</b>	permissible range: 20.4 to 28.8 V
<b>Encoder</b>	
<b>Connectable encoders</b>	
<b>2-wire BEROS</b>	Yes
<b>Integrated Functions</b>	
<b>Number of counters</b>	4
<b>Counter frequency (counter) max.</b>	100 kHz
<b>Frequency meter</b>	Yes
<b>controlled positioning</b>	Yes
<b>PID controller</b>	Yes
<b>Number of alarm inputs</b>	4
<b>Operator control and monitoring</b>	
<b>Display</b>	No
<b>Galvanic isolation</b>	
<b>Galvanic isolation digital inputs</b>	
<b>Galvanic isolation digital inputs between the channels, in groups of</b>	500 VAC for 1 minute 1
<b>Galvanic isolation digital outputs</b>	
<b>Galvanic isolation digital outputs between the channels</b>	Relays No
<b>Galvanic isolation digital outputs between the channels, in groups of</b>	1
<b>Permissible potential difference</b>	
<b>between different circuits</b>	500 VDC between 24 VDC and 5 VDC
<b>EMC</b>	
<b>Interference immunity against discharge of static electricity</b>	
<b>Interference immunity against discharge of static electricity acc. to IEC 61000-4-2</b>	Yes
	8 kV
<b>Test voltage at contact discharge</b>	6 kV
<b>Interference immunity to cable-borne interference</b>	
<b>on the supply lines acc. to IEC 61000-4-4</b>	Yes
<b>Interference immunity on signal lines acc. to IEC 61000-4-4</b>	Yes
<b>Surge immunity</b>	

<b>on the supply lines acc. to IEC 61000-4-5</b>	Yes
<b>Immunity against conducted interference induced by high-frequency fields</b>	
<b>Interference immunity against high-frequency radiation acc. to IEC 61000-4-6</b>	Yes
<b>Emission of radio interference acc. to EN 55 011</b>	
<b>Emission of radio interferences acc. to EN 55 011 (limit class A)</b>	Yes; Group 1
<b>Emission of radio interference acc. to EN 55 011 (limit class B)</b>	Yes
<b>Climatic and mechanical conditions for storage and transport</b>	
<b>Climatic conditions for storage and transport</b>	
<b>Free fall</b>	0.3 m; five times, in dispatch package
<b>Temperature</b>	
<b>Permissible temperature range</b>	-40 °C to +70 °C
<b>Relative humidity</b>	
<b>Permissible range (without condensation) at 25 °C</b>	95%
<b>Mechanical and climatic conditions during operation</b>	
<b>Climatic conditions in operation</b>	
<b>Temperature</b>	5 °C to 55°, 3° C/minute
<b>Air pressure acc. to IEC 60068-2-13</b>	
<b>Permissible air pressure</b>	1080 to 795 hPa
<b>Permissible operating height</b>	-1000m to 2000m
<b>Pollutant concentrations</b>	
	S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
<b>Environmental requirements</b>	
<b>Operating temperature</b>	
<b>Min.</b>	0 °C
<b>max.</b>	55 °C
<b>vertical installation, min.</b>	0 °C
<b>vertical installation, max.</b>	45 °C
<b>horizontal installation, min.</b>	0 °C
<b>horizontal installation, max.</b>	55 °C
<b>Storage/transport temperature</b>	
<b>Min.</b>	-40 °C
<b>max.</b>	70 °C
<b>Air pressure</b>	
<b>Operation, min.</b>	795 hPa
<b>Operation, max.</b>	1080 hPa
<b>Storage/transport, min.</b>	660 hPa
<b>Storage/transport, max.</b>	1080 hPa
<b>Relative humidity</b>	
<b>Operation, max.</b>	95 %; no condensation
<b>Vibrations</b>	
<b>Vibrations</b>	2G panel mount, 1G DIN rail mount
<b>Operation, checked according to IEC 60068-2-6</b>	Yes

<b>Shock test</b>	
<b>checked according to IEC 60068-2-27</b>	Yes; 15 G, 11 ms pulse, 6 shocks in each of 3 axes
<hr/>	
<b>Degree of protection</b>	
<b>IP20</b>	Yes
<hr/>	
<b>Standards, approvals, certificates</b>	
<b>CE mark</b>	Yes
<b>C-TICK</b>	Yes
<b>cULus</b>	Yes
<b>FM approval</b>	Yes
<hr/>	
<b>Dimensions and weight</b>	
<b>Dimensions</b>	
<b>Width</b>	90 mm
<b>Height</b>	100 mm
<b>Depth</b>	75 mm
<hr/>	
<b>Weight</b>	
<b>Weight, approx.</b>	385 g
<hr/>	
<b>Status</b>	Jun 14, 2010
<hr/>	