



SIMATIC S7-1200, CPU 1211C, COMPACT CPU, AC/DC/RELAY,  
ONBOARD I/O: 6 DI 24V DC; 4 DO RELAY 2A; 2 AI 0 - 10V DC,  
POWER SUPPLY: AC 85 - 264 V AC AT 47 - 63 HZ,  
PROGRAM/DATA MEMORY: 50 KB

### General information

Firmware version	V4.1
Engineering with	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 V13 SP1 or higher

### Display

with display	No
--------------	----

### Supply voltage

Rated value (AC)	
<ul style="list-style-type: none"> <li>120 V AC</li> <li>230 V AC</li> </ul>	Yes
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Line frequency	
<ul style="list-style-type: none"> <li>permissible range, lower limit</li> <li>permissible range, upper limit</li> </ul>	47 Hz 63 Hz

### Input current

Current consumption (rated value)	60 mA at 120 V AC; 30 mA at 240 V AC
Current consumption, max.	180 mA at 120 V AC; 90 mA at 240 V AC
Inrush current, max.	20 A; at 264 V

### Encoder supply

24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> </ul>	20.4 to 28.8V

### Output current

for backplane bus (5 V DC), max.	750 mA; Max. 5 V DC for CM
<b>Power losses</b>	
Power loss, typ.	10 W
<b>Memory</b>	
<b>Work memory</b>	
• Integrated	50 kbyte
• expandable	No
<b>Load memory</b>	
• Integrated	1 Mbyte
• Plug-in (SIMATIC Memory Card), max.	with SIMATIC memory card
<b>Backup</b>	
• present	Yes; maintenance-free
• without battery	Yes
<b>CPU processing times</b>	
for bit operations, typ.	0.085 µs; / instruction
for word operations, typ.	1.7 µs; / instruction
for floating point arithmetic, typ.	2.3 µs; / instruction
<b>CPU-blocks</b>	
Number of blocks (total)	DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used
<b>OB</b>	
• Number, max.	Limited only by RAM for code
<b>Data areas and their retentivity</b>	
retentive data area in total (incl. times, counters, flags), max.	10 kbyte
<b>Flag</b>	
• Number, max.	4 kbyte; Size of bit memory address area
<b>Local data</b>	
• per priority class, max.	16 kbyte
<b>Process image</b>	
• Inputs, adjustable	1 kbyte
• Outputs, adjustable	1 kbyte
<b>Hardware configuration</b>	
Number of modules per system, max.	3 communication modules, 1 signal board
<b>Time of day</b>	
<b>Clock</b>	
• Hardware clock (real-time clock)	Yes
• Deviation per day, max.	+/- 60 s/month at 25 °C
• Backup time	480 h; Typical

Digital inputs	
Number of digital inputs	6; Integrated
<ul style="list-style-type: none"> <li>• of which, inputs usable for technological functions</li> </ul>	3; HSC (High Speed Counting)
integrated channels (DI)	6
m/p-reading	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	6
Input voltage	
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• for signal "0"</li> </ul>	5 V DC at 1 mA
<ul style="list-style-type: none"> <li>• for signal "1"</li> </ul>	15 VDC at 2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— Parameterizable	0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— Parameterizable	Yes
for counter/technological functions	
— Parameterizable	Yes; Single phase : 3 at 100 kHz & 3 at 30 kHz, differential: 3 at 80 kHz & 3 at 30 kHz
Cable length	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	500 m; 50 m for technological functions
<ul style="list-style-type: none"> <li>• Unshielded, max.</li> </ul>	300 m; For technological functions: No
Digital outputs	
Number of digital outputs	4; Relays
integrated channels (DO)	4
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	2 A
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	30 W with DC, 200 W with AC
Output delay with resistive load	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> </ul>	10 ms; max.
<ul style="list-style-type: none"> <li>• "1" to "0", max.</li> </ul>	10 ms; max.
Switching frequency	
<ul style="list-style-type: none"> <li>• of the pulse outputs, with resistive load, max.</li> </ul>	1 Hz
Relay outputs	
<ul style="list-style-type: none"> <li>• Number of relay outputs</li> </ul>	4
<ul style="list-style-type: none"> <li>• Number of operating cycles, max.</li> </ul>	mechanically 10 million, at rated load voltage 100,000
Cable length	

- shielded, max. 500 m
- Unshielded, max. 150 m

### Analog inputs

Number of analog inputs	2
Integrated channels (AI)	2; 0 to 10V
<b>Input ranges</b>	
• Voltage	Yes
<b>Input ranges (rated values), voltages</b>	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	≥100k ohms
<b>Cable length</b>	
• shielded, max.	100 m; twisted and shielded

### Analog value creation

<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	10 bit
• Integration time, parameterizable	Yes
• Conversion time (per channel)	625 µs

### Encoder

<b>Connectable encoders</b>	
• 2-wire sensor	Yes

### 1st interface

Interface type	PROFINET
Physics	Ethernet
Isolated	Yes
Automatic detection of transmission speed	Yes
Autonegotiation	Yes
Autocrossing	Yes
<b>Functionality</b>	
• PROFINET IO Device	Yes; Also simultaneously with IO-Device functionality
• PROFINET IO Controller	Yes
<b>PROFINET IO Controller</b>	
• Transmission rate, max.	100 Mbit/s
• Number of connectable IO devices, max.	16
<b>PROFINET IO Device</b>	
<b>Services</b>	
— Shared device	Yes
— Number of IO controllers with shared device, max.	2

### Communication functions

S7 communication	
------------------	--

• supported	Yes
• as server	Yes
• As client	Yes
<b>Open IE communication</b>	
• TCP/IP	Yes
• ISO-on-TCP (RFC1006)	Yes
• UDP	Yes
<b>Web server</b>	
• supported	Yes
• User-defined websites	Yes
<b>Number of connections</b>	
• overall	16; dynamically
<b>Test commissioning functions</b>	
<b>Status/control</b>	
• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
<b>Forcing</b>	
• Forcing	Yes
<b>Diagnostic buffer</b>	
• present	Yes
<b>Traces</b>	
• Number of configurable Traces	2; Up to 512 KB of data per trace are possible
<b>Integrated Functions</b>	
Number of counters	3
Counter frequency (counter) max.	100 kHz
Frequency meter	Yes
controlled positioning	Yes
Number of position-controlled positioning axes, max.	8
PID controller	Yes
Number of alarm inputs	4
<b>Potential separation</b>	
<b>Galvanic isolation digital inputs</b>	
• Potential separation digital inputs	500V AC for 1 minute
• between the channels, in groups of	1
<b>Potential separation digital outputs</b>	
• Potential separation digital outputs	Relays
• between the channels	No
• between the channels, in groups of	1
<b>EMC</b>	
Interference immunity against discharge of static electricity	

• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes
— Test voltage at air discharge	8 kV
— Test voltage at contact discharge	6 kV
<b>Interference immunity to cable-borne interference</b>	
• Interference immunity on supply lines acc. to IEC 61000-4-4	Yes
• Interference immunity on signal lines acc. to IEC 61000-4-4	Yes
<b>Surge immunity</b>	
• on the supply lines acc. to IEC 61000-4-5	Yes
<b>Immunity against conducted interference induced by high-frequency fields</b>	
• Interference immunity against high-frequency radiation acc. to IEC 61000-4-6	Yes
<b>Emission of radio interference acc. to EN 55 011</b>	
• Limit class A, for use in industrial areas	Yes; Group 1
• Limit class B, for use in residential areas	Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011
<b>Degree and class of protection</b>	
Degree of protection to EN 60529	
• IP20	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
<b>Marine approval</b>	
• Marine approval	Yes
<b>Ambient conditions</b>	
Free fall	
• Drop height, max. (in packaging)	0.3 m; five times, in dispatch package
<b>Ambient temperature in operation</b>	
• Min.	-20 °C
• max.	60 °C
• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
<b>Ambient temperature during storage/transportation</b>	
• Min.	-40 °C
• max.	70 °C

<b>Air pressure acc. to IEC 60068-2-13</b>	
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
• Permissible operating height	-1000 to 2000 m
<b>Relative humidity</b>	
• Permissible range (without condensation) at 25 °C	95 %
<b>Vibrations</b>	
• Vibrations	2G wall mounting, 1G DIN rail
• Operation, checked according to IEC 60068-2-6	Yes
<b>Shock test</b>	
• checked according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
<b>Pollutant concentrations</b>	
— SO <sub>2</sub> at RH < 60% without condensation	SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free
<b>programming</b>	
<b>Programming language</b>	
— LAD	Yes
— FBD	Yes
— SCL	Yes
<b>Cycle time monitoring</b>	
• can be set	Yes
<b>Dimensions</b>	
Width	90 mm
Height	100 mm
Depth	75 mm
<b>Weights</b>	
Weight, approx.	420 g
<b>last modified:</b>	17.04.2015