


Modular Cabinet Systems for the electric & electronic industry

- **Superior Quality**
- **Unique Features**
- **Global Listings**
- **Excellent Value**
- **In Stock**

Our standard '0395' stocked cabinets meet requirements for seismic zones 1 and 2 per GR-63-Core. For further information and how to modify for zones 3 and 4, please contact us.

Surface finish

- Powder coated (Epoxy-Polyester) RAL 7035 texture finish



Lock

- 4-point latch lock
- "Roll-in" mechanism for reliable & smooth operation

International ratings

- IP 55 / Type 12
- NEMA 3R rain-shields stocked + available as option

Modular design

- Welded construction
- Removable side + back walls
- Most stable cabinet of its kind in the market
- Tested successfully with over 3000 lbs
- Easy to customize
- 4" and 8" bases available



Convenience hinges

- Robust metal hinges
- Tool-less lift-off design,
- Opening angle 120° (180° hinges available as option)

Seal

- Seamless foamed-in-place gasket

Safe and convenient mounting plate installation



Attachment brackets with "snap-in device" at top



Plastic sliders on rails for easy movement at bottom



US-Stocked Sizes!



hawa 0395 modular cabinets
powder coated (Epoxy-Polyester) RAL 7035, texture finish

DON'T FIND THE SIZE YOU NEED? PLEASE CONTACT HAEWA FOR ANY MODIFICATION OR CUSTOMIZATION AT 1-800-783-4239	Size [inches]	Size [mm]	Order No. ^{(1) (4)}	Order No. ⁽²⁾	Mounting Plate		Usable Depth	Weight
	H x W x D	H x W x D	Cabinet	Pair of side panels	H x W			
	(nominal)	(exact)	incl. mounting plate		in	mm	in / mm	lbs / kg
20" deep Type 12 / IP 55 <small>(16" deep cabinets available also! Please contact customer service for lead times.)</small>	71 x 16 x 20	1800 x 400 x 500	0397-4018-50-17	0396-7018-50-67	66.14 x 14.44	1680 x 316	17.01 / 432	150 / 68
	71 x 24 x 20	1800 x 600 x 500	0395-6018-50-17	0396-7018-50-67	66.14 x 20.31	1680 x 516	17.01 / 432	199 / 90
	71 x 32 x 20	1800 x 800 x 500	0395-8018-50-17	0396-7018-50-67	66.14 x 28.19	1680 x 716	17.01 / 432	247 / 112
	71 x 40 x 20	1800 x 1000 x 500	0395-1018-50-17	0396-7018-50-67	66.14 x 36.06	1680 x 916	17.01 / 432	309 / 140
	71 x 48 x 20	1800 x 1200 x 500	0395-1218-50-17 ⁽³⁾	0396-7018-50-67	66.14 x 43.94	1680 x 1116	17.01 / 432	369 / 167
	79 x 16 x 20	2000 x 400 x 500	0397-4020-50-17	0396-7020-50-67	74.02 x 14.44	1880 x 316	17.01 / 432	163 / 74
	79 x 24 x 20	2000 x 600 x 500	0395-6020-50-17	0396-7020-50-67	74.02 x 20.31	1880 x 516	17.01 / 432	217 / 98
	79 x 32 x 20	2000 x 800 x 500	0395-8020-50-17	0396-7020-50-67	74.02 x 28.19	1880 x 716	17.01 / 432	270 / 122
	79 x 40 x 20	2000 x 1000 x 500	0395-1020-50-17	0396-7020-50-67	74.02 x 36.06	1880 x 916	17.01 / 432	336 / 152
	79 x 48 x 20	2000 x 1200 x 500	0395-1220-50-17 ⁽³⁾	0396-7020-50-67	74.02 x 43.94	1880 x 1116	17.01 / 432	402 / 182
24" deep Type 12 / IP 55	63 x 24 x 24	1600 x 600 x 600	0395-6016-60-17	0396-7016-60-67	58.27 x 20.31	1480 x 516	20.94 / 532	188 / 85
	63 x 32 x 24	1600 x 800 x 600	0395-8016-60-17	0396-7016-60-67	58.27 x 28.19	1480 x 716	20.94 / 532	234 / 106
	71 x 16 x 24	1800 x 400 x 600	0397-4018-60-17	0396-7018-60-67	66.14 x 14.44	1680 x 316	20.94 / 532	157 / 71
	71 x 24 x 24	1800 x 600 x 600	0395-6018-60-17	0396-7018-60-67	66.14 x 20.31	1680 x 516	20.94 / 532	206 / 93
	71 x 32 x 24	1800 x 800 x 600	0395-8018-60-17	0396-7018-60-67	66.14 x 28.19	1680 x 716	20.94 / 532	254 / 115
	71 x 40 x 24	1800 x 1000 x 600	0395-1018-60-17	0396-7018-60-67	66.14 x 36.06	1680 x 916	20.94 / 532	318 / 144
	71 x 48 x 24	1800 x 1200 x 600	0395-1218-60-17 ⁽³⁾	0396-7018-60-67	66.14 x 43.94	1680 x 1116	20.94 / 532	378 / 171
	79 x 16 x 24	2000 x 400 x 600	0397-4020-60-17	0396-7020-60-67	74.02 x 14.44	1880 x 316	20.94 / 532	172 / 78
	79 x 24 x 24	2000 x 600 x 600	0395-6020-60-17	0396-7020-60-67	74.02 x 20.31	1880 x 516	20.94 / 532	221 / 100
	79 x 32 x 24	2000 x 800 x 600	0395-8020-60-17	0396-7020-60-67	74.02 x 28.19	1880 x 716	20.94 / 532	276 / 125
	79 x 40 x 24	2000 x 1000 x 600	0395-1020-60-17	0396-7020-60-67	74.02 x 36.06	1880 x 916	20.94 / 532	344 / 156
	79 x 48 x 24	2000 x 1200 x 600	0395-1220-60-17 ⁽³⁾	0396-7020-60-67	74.02 x 43.94	1880 x 1116	20.94 / 532	411 / 186
	87 x 24 x 24	2200 x 600 x 600	0395-6022-60-17	0396-7022-60-67	81.89 x 20.31	2080 x 516	20.94 / 532	239 / 108
	87 x 32 x 24	2200 x 800 x 600	0395-8022-60-17	0396-7022-60-67	81.89 x 28.19	2080 x 716	20.94 / 532	296 / 134
87 x 40 x 24	2200 x 1000 x 600	0395-1022-60-17	0396-7022-60-67	81.89 x 36.06	2080 x 916	20.94 / 532	371 / 168	
87 x 48 x 24	2200 x 1200 x 600	0395-1222-60-17 ⁽³⁾	0396-7022-60-67	81.89 x 43.94	2080 x 1116	20.94 / 532	441 / 200	
32" deep Type 12 / IP 55	79 x 24 x 32	2000 x 600 x 800	0395-6020-80-17	0396-7020-80-67	74.02 x 20.31	1880 x 516	28.82 / 732	276 / 125
	79 x 32 x 32	2000 x 800 x 800	0395-8020-80-17	0396-7020-80-67	74.02 x 28.19	1880 x 716	28.82 / 732	305 / 138
	79 x 40 x 32	2000 x 1000 x 800	0395-1020-80-17	0396-7020-80-67	74.02 x 36.06	1880 x 916	28.82 / 732	378 / 171
	87 x 24 x 32	2200 x 600 x 800	0395-6022-80-17	0396-7022-80-67	81.89 x 20.31	2080 x 516	28.82 / 732	256 / 116
	87 x 32 x 32	2200 x 800 x 800	0395-8022-80-17	0396-7022-80-67	81.89 x 28.19	2080 x 716	28.82 / 732	320 / 145
	87 x 40 x 32	2200 x 1000 x 800	0395-1022-80-17	0396-7022-80-67	81.89 x 36.06	2080 x 916	28.82 / 732	400 / 181
	87 x 48 x 32	2200 x 1200 x 800	0395-1222-80-17	0396-7022-80-67	81.89 x 43.94	2080 x 1116	28.82 / 732	480 / 218

(1) Type 0395 cabinets with these order numbers include mounting plates; if mounting plate is not required, please order number ending in "-07"
(2) Due to the modular design of this cabinet range, side panels are not included. Please order one pair of side panels for each cabinet group.
(3) Two overlapping doors
(4) For hinged front and back doors use "X2-17"

Bases for above cabinets

Mild steel, powder coated (Epoxy-Polyester) RAL 7022, texture finish

4" / 100 mm high	Part number: 0396-WW01-DD-17	with	WW = 60	for width of	24" / 600 mm
			WW = 80	for width of	32" / 800 mm
8" / 200 mm high	Part number: 0396-WW02-DD-17		WW = 10	for width of	40" / 1000 mm
			WW = 12	for width of	48" / 1200 mm
		and	DD = 40	for depth of	16" / 400 mm
			DD = 50	for depth of	20" / 500 mm
			DD = 60	for depth of	24" / 600 mm
			DD = 80	for depth of	32" / 800 mm